

TimeTools T300 time server is a cost-effective, accurate, Stratum-1 GPS referenced Network Time Protocol Server in a 1U rack-mountable enclosure.

It provides an accurate time reference to computer networks and can accurately synchronize any NTP or SNTP compatible system.



Highlights

NTPv4 Stratum-1 GPS Network Time Server.

GPS accurate to 15 nanoseconds (GPS Locked).

NTP accurate to 3 microseconds (GPS Locked).

Synchronize in excess of 2 million clients.

10/100 Mbit auto-sensing, auto-MDIX Ethernet port.


IPv4 and IPv6 Internet Protocols.

Simple Network Management Protocol Monitoring (SNMP v3).

Extremely cost-effective.

Integrated universal AC mains input PSU.

Made in UK.



Applications

- Network timing, measurement and synchronization.
- Synchronize Microsoft Windows, Linux, servers, workstations and network infrastructure.
- Automation Systems, SCADA, Network Monitoring and Control Systems.
- CCTV, DVR and Video Management Systems (VMS).
- Access Control Systems (ACS).
- Master clock for NTP synchronized clock systems.
- Accurately synchronize time critical processes to a traceable source of time inside your firewall.

Key Features and Benefits

- Linux based true stratum-1 NTP time server.
- Extremely easy to install and configure.
- Simple web based configuration and status information.
- High-quality, 1U high, 19" rack-mountable aluminium enclosure.
- Large back-lit LCD display shows detailed status information.
- USB port for convenient firmware updates.

GPS Timing Features

- 16 channel, high-sensitivity, GPS timing receiver with single-satellite in view operation.
- Operation with outdoor, indoor or window located antenna with limited sky view, saving on cabling costs.
- Timing receiver synchronizes to 15 nanoseconds (15×10^{-9} sec, 1 sigma, GPS locked).
- Time-Receiver Autonomous Integrity Monitoring (T-RAIM) assures very high timing integrity.
- Fully automatic impending leap second warning and insertion, no user intervention required.
- Jam-resistant signal reception.

NTP Timing Features

- NTP synchronization to <3 microsecond (3×10^{-6} sec) UTC (GPS Locked).
- Ability to synchronize in excess of 2 million clients at default NTP polling frequency.
- Peer to multiple external and internet based NTP servers.
- Authentication for enhanced security.

Reliable and Environmentally Friendly

- Based on extremely reliable industrial computing module.
- Very low-power consumption, less than 7W.
- RoHS compliant - Restriction on use of hazardous substances.

Networking Features

- 10/100 Mbit Auto-Sensing, Auto-MDIX Ethernet port.
- NTPv4, SNTPv4, HTTP, HTTPS, SSH, SCP, SFTP, FTP, SNMPv3, DHCP, DHCPv6.
- IPv4 and IPv6 Internet Protocol.

Warranty and Support

- 3-year warranty.
- Free unlimited support and firmware updates for the lifetime of the product.

Product Specification

Interfaces

10/100 Mbit Base-T, RJ45, Auto-Sensing Network Interface.
TNC RF Connector For Active GPS Antenna.
USB port for firmware updates.
RS232 Console Port for Configuration and Status.
Second RS232 (shared) Port for serial time code output.

Operating System

Flash-Based Linux Operating System with PPS Extensions.

Internet Protocol (IP)

IPv4, IPv6.

Timing Protocols

NTP v2 (RFC 1119), NTP v3 (RFC 1305), NTP v4 (RFC 5905).
SNTP v3 (RFC 1769), SNTP v4 (RFC 2030).
NTP Peering, NTP Broadcast.
NTP Authentication.
Max. NTP Polling Freq.: 2000 polls per second.
Max. Clients at Default NTP Polling Freq.^{*1}: 2,000,000

Configuration and Monitoring Protocols

HTTP, HTTPS, SSH, SCP, SFTP, FTP.
SNMP: v1, v2c, v3
Dynamic Host Configuration Protocol - DHCP (RFC 2131).
Dynamic Host Configuration Protocol - DHCPv6 (RFC 3315).

Timing (typical)

GPS Accuracy: 15 nanoseconds (15×10^{-9} sec, GPS Lock)
NTP Accuracy (GPS Lock): <3 microsecond (3×10^{-6} sec)



GPS Timing Receiver

16 Channel GPS Receiver.
Time-Receiver Autonomous Integrity Monitoring.
High Sensitivity Outdoor/Indoor Antenna Operation.
Over-Determined Clock, Single Satellite Operation.

Positioning System: SPS, Timing
Update Rate: 1 Hz
Freq. Band: GPS L1
Typical Min Acquisition Sensitivity: -148dBm cold start
Typical Min Tracking Sensitivity: -160dBm
Time to First Fix: <46s (50%), <50s (90%) cold start
Typical Time to Re-acquisition: <2s (90%)

Mechanical \ Environmental

Dimensions: 483 x 145 x 44 mm (19.0" x 5.71" x 1.73")
Construction: 1U High 19" Rack-mount, Aluminium
Weight: approx 1.2Kg (2.6lbs)

Power: 100-240VAC 50-60Hz 0.1A
Fuses: Two, T0.315A LBC 250V
Power Consumption: <7W
Double Fused IEC Inlet

Operating Temperature 0°C ~ +50°C
Storage Temperature -20°C ~ +85°C
Working Humidity 90% RH non-condensing

T-3040 GPS Antenna Specification

Freq. Band: 1575 MHz \pm 10 MHz
Size: 66.5mm diameter x 21mm High
Weight: 150g
Enclosure: Radome: EXL9330, Base: Zamak White Metal
Attachment Method: Through hole (M18 x 1 thread)
Environmental: IP67
Operating Temperature: -40°C ~ +85°C

LNA Gain: 40 dB typical.
Supply Current: 19mA typical.
Supply Voltage: 2.5 to 12 VDC nominal

Approvals

CE: 2014/53/EU
2011/65/EU
2015/863/EU
Radio: EN 300 440 V2.1.1
EMC: EN 55032: 2012 +AC: 2013
EN 55024: 2010
EN 61000-3-2: 2014
EN 61000-3-3: 2013
Safety: EN 60950-1: 2006+A2: 2013
EN 62368-1:2014/AC:2015
RoHS: EN 50581:2012

Ordering Information

Product Codes

T300-00 GPS NTP Server appliance.

Scope of Supply – What is Included

T300 GPS NTP Server Appliance.
T-3040 Pole Mounting GPS Antenna .
MT4-GPS Antenna Mount.
TCX-030 30m (100 ft) LMR195 Equivalent Cable.

IEC Power Lead.
RS232 Serial Console Cable.
Quick Start Guide.
CD containing user-guide, installation guide and white-papers.

Optional Accessories

TCX-010 10m LMR195 Equivalent Cable.
TCX-030 30m LMR195 Equivalent Cable.
TCX-050 50m LMR195 Equivalent Cable.
TCX-100 100m LMR400 Equivalent Cable.
Custom cable lengths available on request.

SPP-GPS Multi-strike maintenance-free surge suppressor
T-AD200-8 GPS Amplifier – 20db

Digital NTP Wall clocks.
Analog NTP Wall clocks.

*1. Assuming default 1024 sec client NTP polling frequency. Even more clients can be synchronized by decreasing the polling frequency.

TimeTools Limited has relied on representations made by its suppliers in certifying this product as RoHS compliant.

TimeTools Limited is not responsible for the availability, operation or failure of operation of GPS/GNSS satellites.

In no event will TimeTools Limited be liable for any indirect, special, incidental, or consequential damages from the sale or use of this product. This disclaimer applies both during and after the term of the warranty. TimeTools Limited disclaims liability for any implied warranties, including implied warranties of merchantability and fitness for a specific purpose.

All specifications subject to change without notice.

Terms and conditions of sale available on request.

Registered trademarks acknowledged. All rights reserved.

© 2020 TimeTools Limited. All Rights Reserved.

Contact Information

TimeTools Limited.
2 Silverend Business Park,
Brettell Lane,
Brierley Hill. DY5 3LG.
UK.

Phone: +44 (0) 1902 897400
Fax: +44 (0) 870 123 1844
Email : Sales@TimeToolsLtd.com
Web: <https://TimeToolsLtd.com/>